## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	: LEDVANCE

Supplier's address: LEDVANCE GmbH, Parkring 29-33, 85748 Garching, DE

Model identifier: AC27630

Type of light sou	ırce:	:
-------------------	-------	---

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	B22d		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Draduct parameters			

## **Product parameters**

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
Energy consur mode (kWh/10 up to the neare	00 h), rounded	9	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27006500
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,50
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	115	Spectral power dis-	See image
sions without	Width	60	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	60
		Chromaticity coordinates (x and y)	0,463 0,420
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,70		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)'-': not applicable; (b)'-': not applicable;

